



Plug Tag



LOW FREQUENCY RFID TAGS ENABLE IMPROVED TRACKING OF PLASTIC WASTE BINS AND CONTAINERS

- **Easily integrated, yet tamper resistant** – inserts securely into standard pre-drilled holes in waste bins and containers
- **Sturdy** – resistant to liquids, thermal fluctuation, vibration and shock
- **Unsurpassed quality** – fully automated HID manufacturing and direct-bonding technology ensure dependable performance

HID Plug Tag transponders enable the cost-effective tagging of plastic residential, commercial and industrial waste containers for tracking usage via radio frequency identification (RFID).

Automated tracking accelerates waste management processes, and enables pay-as-you-throw and recycling incentive programs, while eliminating error-prone and expensive manual data collection methods historically used for these systems.

The durable Plug Tag housing protects embedded electronics, delivering reliable performance in harsh waste management and logistics environments. Each tag is completely waterproof, and consistently readable, even when temperatures dip

to -13° F (-20° C) or rise to 185° F (85° C). Ridges around the shaft ensure that the RFID tag inserts easily, yet is locked securely into place to prevent tag loss or removal in the field. Plug Tag transponders include read-only memory, in 64 bit UID or 128 bit FDX-b options.

For metallic containers, the HID Bin Tag and IN Tag families include tags that deliver consistent, reliable performance when mounted on metal. In addition, these lines include high frequency and UHF chip options, and available read-write memory up to 2048 bits.

HID will help identify and provide the optimal RFID transponder choice for your application.

TECHNOLOGY HIGHLIGHTS:

- 100% waterproof (IP68)
- Height 0.75 in (19 mm), with diameters of:
 - 0.35 in (9 mm) - shaft
 - 0.59 in (15 mm) - cap
- Integrated chip options:
 - Unique, 131 kHz, 64 bit read-only memory
 - FDX-b, 134.2 kHz, 128 bit read-only

APPLICATION AREAS:

- **Waste management**
 - Residential, commercial and industrial waste bin tracking
 - Recycling compliance monitoring
 - Improved invoicing and service accuracy
 - Route optimization systems
 - Incentive-based waste and recycling programs
- **Returnable transport items**
 - Perishable produce crates
 - Stock system bins



HID can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

SPECIFICATIONS

| | Plug Tag | |
|--------------------------------|--|-------------------|
| | Unique | FDX-b |
| Base Model Number | 601920-001 | 684921-002 |
| ELECTRONIC | | |
| Operating Frequency | 131 kHz ± 6 | 134.2 kHz ± 6 |
| Chip Type | Unique | FDX-b BDE |
| Memory | 64 bit read-only | 128 bit read-only |
| PHYSICAL | | |
| Dimensions | Ø 0.35 x 0.75 in, cap Ø 0.59 in (Ø 9 x 19 mm, cap Ø 15 mm) | |
| Mounting Method | Insert into pre-drilled hole | |
| Affixes To | Plastic | |
| Housing Material | PA6 | |
| Color | Black | |
| CHEMICAL AND MECHANICAL | | |
| Water | IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h | |
| Vibration | IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h] | |
| Shock | IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times] | |
| THERMAL | | |
| Storage | -13° to +185° F (-20° to 85° C), 1000 h | |
| Operating Temperature | -13° to +185° F (-20° to 85° C) | |
| OTHER | | |
| Standards | EN 14803, ISO 11785 | |
| Options | Alternative colors | |
| Warranty | 7 Years | |

North America: +1 949 732 2000
 Toll Free: 1 800 237 7769
 Europe, Middle East, Africa: +41 21 908 01 00
 Asia Pacific: +852 3160 9800
 Latin America: +52 55 5081-1650

hidglobal.com

ASSA ABLOY

An ASSA ABLOY Group brand

© 2012 HID Global Corporation. All rights reserved. HID, the HID logo and ceFLEX are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.
 2012-01-11-hid-rfid-il-plug-tag-ds-en